


FRIGO SOPRA BANCO

COUNTERTOP DISPLAY COOLER



CL 46 FL WHT

Frigo bibite sopra banco statico con agitatore
Static-fan assisted countertop display cooler



CL 46 FL BLK

Frigo bibite sopra banco statico con agitatore
Static-fan assisted countertop display cooler

Capienza / Capacity

Bottiglia cl. 50 / Bottle cl. 50

22

Lattina cl. 33 / Can cl. 33

40

Dati indicativi e variabili a seconda dei diversi packaging / Variable data depending on the different packaging




Interno in ABS termoformato
Thermoformed ABS inner liner



Termostato digitale
Digital thermostat



Porta vetro senza cornice
Full glass frameless door



Dimensioni mm / Dimensions mm	CL 46 FL
Dimensioni Esterne (LxPxH) / External Dimensions (WxDxH)	475 x 435 x 520
Dimensioni Imballo (LxPxH) / Packaging Dimensions (WxDxH)	520 x 465 x 535
A - Larghezza / Width	402
B - Profondità / Depth	360
C - Altezza / Height	421
D - Profondità Min. / Min. Depth	178
E - Altezza Min. / Min. Height	232
Adesivo Laterale / Side Sticker	383 x 480
Adesivo Vetro / Glass Sticker	326 x 339

Caratteristiche Tecniche / Technical Features	CL 46 FL
Temperatura / Temperature Range	+2 °C / +10 °C
Classe Climatica / Climate Class	4
Volume Netto-Lordo / Net-Gross Volume	Lt. 46 / 48
Superficie Esterna Body	ABS
Porta / Door	Porta vetro senza cornice Full glass frameless door
Superficie Interna / Inner Liner	ABS
Termostato / Thermostat	Elettronico / Electronic
Rumorosità / Noise level	dB 42
Spessore isolamento / Insulation thickness	mm 40
Sbrinamento Defrost	Manuale / Manual
Illuminazione Lighting	1 Led sul lato superiore 1 Led on top side
Reversibilità porta / Reversible door	No
Mensole (LxP) / Shelves (WxD)	N° 1 - mm 393 x 105
Ruote-Piedi / Castors-Feet	4 Piedi / 4 Feet
Peso Netto-Lordo / Net-Gross Weight	Kg 18 / 21
Voltaggio / Voltage	V 220
Frequenza / Frequency	Hz 50
Refrigerante / Refrigerant	R600A
Assorbimento / Absorption	W 80
Consumo Energia / Energy Consumption	Kwh/24H 0,83