

CONGELATORI A POZZO

CHEST FREEZER



Compressore INVERTER.
INVERTER compressor.



GELO 350 PS

Congelatore statico a pozzo porta cieca battente.
Static chest freezer with solid hinged lids.



GELO 550 PS

Congelatore statico a pozzo porta cieca battente.
Static chest freezer with solid hinged lids.

GELO 450 PS

Congelatore statico a pozzo porta cieca battente.
Static chest freezer with solid hinged lids.

GELO 650 PS

Congelatore statico a pozzo porta cieca battente.
Static chest freezer with solid hinged lids.



GELO 750 PS

Congelatore statico a pozzo doppia porta cieca battente.
Static chest freezer with double solid hinged lids.








Chiave e serratura
Lock and key



Interno lamiera preverniciata bianca
White prepainted sheet innerliner



Termostato e termometro meccanico
Mechanical thermostat and thermometer



Dimensioni mm / Dimensions mm	GELO 350 PS	GELO 450 PS	GELO 550 PS	GELO 650 PS	GELO 750 PS
Dimensioni Esterne (LxPxH) External Dimensions (WxDxH)	1035 x 750 x 880	1275 x 750 x 880	1535 x 750 x 880	1805 x 750 x 880	2075 x 750 x 880
Dimensioni Imballo (LxPxH) Packaging Dimensions (WxDxH)	1080 x 760 x 980	1320 x 760 x 980	1580 x 760 x 980	1850 x 760 x 980	2125 x 760 x 980
A - Larghezza / Width	890	1130	1390	1660	1930
B - Profondità / Depth	530	530	530	530	530
C - Altezza / Height	665	665	665	665	673
E - Altezza Minima / Min. Height	415	415	415	415	423
F - Larghezza Minima / Min. Width	660	900	1160	1430	1700
Adesivo Laterale Destro / Side Right Sticker	670 x 530	670 x 530	670 x 530	670 x 530	670 x 530
Adesivo Laterale Sinistro / Side Left Sticker	670 x 762	670 x 762	670 x 762	670 x 762	670 x 762
Adesivo Frontale / Front Sticker	1030 x 762	1270 x 762	1530 x 762	1800 x 762	2070 x 762

Caratteristiche Tecniche / Technical Features	GELO 350 PS	GELO 450 PS	GELO 550 PS	GELO 650 PS	GELO 750 PS
Temperatura / Temperature Range	-23 °C / -10 °C	-23 °C / -10 °C	-23 °C / -10 °C	-23 °C / -10 °C	-23 °C / -10 °C
Classe Climatica / Climate Class	4	4	4	4	4
Volume Netto-Lordo / Net-Gross Volume	Lt. 283 / 304	Lt. 368 / 383	Lt. 459 / 473	Lt. 560 / 567	Lt. 598 / 670
Superficie Esterna Body	Lamiera preverniciata con trattamento anticorrosione Prepainted sheet with anticorrosion treatment				
Superficie Interna Inner Liner	Lamiera preverniciata bianca con trattamento anticorrosione, con rivestimento in poliestere verniciato bianco White prepainted sheet with anticorrosion treatment, coating with white paint Polyester				
Cestelli / Baskets	Standard 1 pz / 1 pcs 573 x 245 x 248 mm	Standard 2 pz / 2 pcs 573 x 245 x 248 mm	Standard 2 pz / 2 pcs 573 x 245 x 248 mm	Standard 2 pz / 2 pcs 573 x 245 x 248 mm	Standard 2 pz / 2 pcs 573 x 245 x 248 mm
Termometro / Thermometer	Meccanico Mechanical	Meccanico Mechanical	Meccanico Mechanical	Meccanico Mechanical	Meccanico Mechanical
Regolatore temperatura / Controller	Meccanico Mechanical	Meccanico Mechanical	Meccanico Mechanical	Meccanico Mechanical	Meccanico Mechanical
Rumorosità / Noise level	dB 48	dB 50	dB 50	dB 50	dB 51,4
Compressore / Compressor	Inverter	Inverter	Inverter	Inverter	Inverter
Spessore isolamento / Insulation thickness	mm 70	mm 70	mm 70	mm 70	mm 70
Sbrinamento / Defrost	Manuale / Manual	Manuale / Manual	Manuale / Manual	Manuale / Manual	Manuale / Manual
Chiave e serratura / Lock and key	Si / Yes	Si / Yes	Si / Yes	Si / Yes	Si / Yes
Illuminazione led / Led lighting	Si / Yes	Si / Yes	Si / Yes	Si / Yes	
Ruote-Piedi / Castors-Feet	4 Ruote h 70mm, 2 con freni 4 Castors h 70mm, 2 with brake				
Peso Netto-Lordo / Net-Gross Weight	Kg 43 / 57	Kg 52 / 65	Kg 63 / 82	Kg 68 / 91	Kg 80 / 106
Voltaggio / Voltage	V 220	V 220	V 220	V 220	V 220 / 240
Frequenza / Frequency	Hz 50	Hz 50	Hz 50	Hz 50	Hz 50
Refrigerante / Refrigerant	R600A	R600A	R600A	R600A	R290
Assorbimento / Absorption	W 90	W 125	W 125	W 125	W 185
Consumo Energia / Energy Consumption	KwH/24H 2,27	KwH/24H 2,603	KwH/24H 3,005	KwH/24H 3,450	KwH/24H 3,723